

With focus on detail. Designed to yield maximum clarity, when dealing with fast transients and abundant high frequency content.


- **Balanced, transformerless**
- **-12 dB pre-attenuation**
- **12 - 52 V phantom**
- **Fits direct to mixer, XLR-amp.**

Frequency response (see graph)	20 - 20 000 Hz
Polar pattern	Cardioid
Pre-attenuation (switchable)	-12 dB
Max. SPL (1% THD at 1 kHz)	128 / 140 dB
Sensitivity at 1kHz	14,5 mV / Pa \pm 1 dB
A-weighted noise level	21 dB
Power supply (DIN 45 596)	12 - 52 V
Current consumption	4 mA
Output impedance	< 200 Ω
Minimum load impedance	1 k Ω
Link cable length	3 m
Connection	3-pin XLR pin 1: earth (Shield) pin 2: plus (Hot) pin 3: minus (Cold)


	<i>Active Cap.</i>	<i>XLR-amp.</i>
Net weight	50 g	85 g
Length	49 mm	105 mm
Diameter	21 mm	19 mm

Frequency response (at 1m distance)

The frequency response may vary within $\pm 2,5$ dB of the published graph.
Before delivery, each microphone is measured and accompanied with it's own graph.



Polar diagram



Milab Microphones AB

Mailing address
P. O. Box 1342
S-251 13 HELSINGBORG
SWEDEN

Office address
Norra Strandgatan 4

Phone
+46 42 381620

Fax
+46 42 136350

E-mail
milab@milabmic.com
Internet
www.milabmic.com